

# KSB AmaDrainer A 422 SD/10

Submersible drainage pump | 3 x 400 V / 50 Hz  
Reference 29128746

Vertical single-stage pump for draining basements, pits and collecting tanks. Standard A version with float switch and without cooling jacket.

## Technical data

|                                |                                 |
|--------------------------------|---------------------------------|
| Power supply                   | 3 x 400 V / 50 Hz               |
| Input power P1                 | 2.90 kW                         |
| Rated power P2                 | 2.20 kW                         |
| Free passage                   | 10 mm                           |
| Discharge                      | G 1 1/2                         |
| Power cable                    | 10 m   6 x 1.00 mm <sup>2</sup> |
| Net weight                     | 16.9 kg                         |
| Protection / maximum immersion | IP68 / 7 m                      |
| Float switch                   | Included                        |
| Cooling jacket                 | Without                         |

## Use and selection

For clean water and wastewater without faecal matter, with solids up to 10 mm. Liquid temperature up to 40 °C in continuous operation; up to 90 °C for a maximum of 3 minutes. Three-phase version with float switch. Float cable: 10 m, 3 x 1.00 mm<sup>2</sup>. Confirm the correct electrical connection and protection for the installation.

Check the duty point against the KSB performance curves and confirm suitability for the installation before ordering. Do not select this version for seawater or aggressive liquids. Shipping weight including packaging to be confirmed.